

NEOPRENE (CR)

COMMERCIAL GRADE PLATE FINISH IM-262

FEATURES

- Natural aging to alkalis and acids
- Good resistance to abrasion and flex cracking

GRADE	Commercial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Black

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
202-04-362	1/16 (1.59)	36 (914.4)	300 (27.87)	100 (30.48)	143 (64.6)
202-04-482	1/16 (1.59)	48 (1219.2)	400 (37.15)	100 (30.48)	190 (86.2)
202-06-362	3/32 (2.38)	36 (914.4)	225 (20.9)	75 (22.86)	160 (72.8)
202-06-482	3/32 (2.38)	48 (1219.2)	300 (27.87)	75 (22.86)	214 (97)
202-08-362	1/8 (3.17)	36 (914.4)	150 (13.93)	50 (15.24)	143 (64.7)
202-08-482	1/8 (3.17)	48 (1219.2)	200 (18.58)	50 (15.24)	190 (86.3)
202-08-722	1/8 (3.17)	72 (1828.8)	210 (19.51)	35 (10.66)	200 (90.6)
202-12-362	3/16 (4.76)	36 (914.4)	120 (11.15)	40 (12.19)	171 (77.6)
202-12-482	3/16 (4.76)	48 (1219.2)	160 (14.85)	40 (12.19)	228 (103.5)
202-16-362	1/4 (6.35)	36 (914.4)	120 (11.15)	40 (12.19)	228 (103.5)
202-16-482	1/4 (6.35)	48 (1219.2)	160 (14.85)	40 (12.19)	304 (138)
202-16-722	1/4 (6.35)	72 (1829)	240 (22)	40 (12.19)	434 (196.9)
202-24-362	3/8 (9.52)	36 (914.4)	90 (8.36)	30 (9.14)	254 (115.2)
202-24-482	3/8 (9.52)	48 (1219.2)	120 (11.15)	30 (9.14)	339 (153.6)
202-32-362	1/2 (12.70)	36 (914.4)	90 (8.36)	30 (9.14)	339 (153.6)
202-32-482	1/2 (12.70)	48 (1219.2)	120 (11.15)	30 (9.14)	453 (205.3)
202-40-362	5/8 (15.90)	36 (914.4)	90 (8.36)	30 (9.14)	425 (192.8)
202-40-482	5/8 (15.90)	48 (1219.2)	120 (11.15)	30 (9.14)	567 (257.1)
202-48-362	3/4 (19.00)	36 (914.4)	90 (8.36)	30 (9.14)	511 (231.5)
202-48-482	3/4 (19.00)	48 (1219.2)	120 (11.15)	30 (9.14)	681 (308.8)
202-64-362	1 (25.40)	36 (914.4)	90 (8.36)	30 (9.14)	679 (308)
202-64-482	1 (25.40)	48 (1219.2)	100 (9.29)	25 (7.62)	755 (342.2)

¹ Made-to-order.



TECHNICAL SPECIFICATIONS IM-262

SPECIFICATION ASTM D2240 HARDNESS 60 ±7 (Shore A)
POLYMER: Neoprene® (CR) Blend

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (Shore A)	60
D412	TENSILE (psi)	500 nom.
	ULTIMATE ELONGATION (%)	300 nom.
TEMPERATURE RANGE (general guideline)		-20° to 190° F (-29° to 88° C)
Width tolerance: +/- 0.5"		
Length tolerance: +/- 10%		
Durometer tolerance:± 7 points		
Material is within RMA commercial gauge tolerances.		

Please ensure the product meets your application specification prior to order placement.
Specifications are subject to change without notice. The website version prevails.