

SBR (PACKING/SKIRTBOARD)

IM-618

FEATURES

- Industrial blend SBR for gaskets

GRADE	Industrial
FINISH	Smooth
POWDER	No
TRIMMED	Yes
COLOR	Red

	GAUGE IN (MM)	WIDTH IN (MM)	SURFACE/ROLL SFT (M ²)	LENGTH/ROLL LFT (M)	WEIGHT/ROLL LBS (KG)
110-04-368	1/16 (1.59)	36 (914.4)	210 (19.51)	70 (21.33)	119 (54)
110-04-488	1/16 (1.59)	48 (1219.2)	200 (18.58)	50 (15.24)	113 (51.3)
110-04-728 ¹	1/16 (1.59)	72 (1828.8)	420 (39.02)	70 (21.33)	222 (100.8)
110-06-368 ¹	3/32 (2.38)	36 (914.4)	165 (15.33)	55 (16.76)	140 (63.5)
110-06-488 ¹	3/32 (2.38)	48 (1219.2)	160 (14.86)	40 (12.19)	136 (61.7)
110-06-728 ¹	3/32 (2.38)	72 (1828.8)	330 (30.66)	55 (16.76)	262 (118.9)
110-08-368	1/8 (3.17)	36 (914.4)	105 (9.75)	35 (10.66)	119 (54)
110-08-488	1/8 (3.17)	48 (1219.2)	100 (9.29)	25 (7.62)	113 (51.3)
110-08-728	1/8 (3.17)	72 (1828.8)	210 (19.51)	35 (10.66)	222 (100.7)
110-12-368 ¹	3/16 (4.76)	36 (914.4)	150 (13.93)	50 (15.24)	254 (115.2)
110-12-488 ¹	3/16 (4.76)	48 (1219.2)	140 (13)	35 (10.66)	237 (107.5)
110-12-728 ¹	3/16 (4.76)	72 (1828.8)	150 (13.93)	25 (7.62)	238 (108)
110-16-368	1/4 (6.35)	36 (914.4)	105 (9.75)	35 (10.66)	237 (107.5)
110-16-488	1/4 (6.35)	48 (1219.2)	100 (9.29)	25 (7.62)	226 (102.5)
110-16-728 ¹	1/4 (6.35)	72 (1828.8)	120 (11.15)	20 (6.09)	254 (115.2)

¹ Made-to-order.



TECHNICAL SPECIFICATIONS IM-618

SPECIFICATION ASTM D2240 HARDNESS 75 ±7 (Shore A)
POLYMER: Styrene-Butadiene (SBR) (Red)

ASTM	DESCRIPTION	VALUE
D2240	HARDNESS (Shore A)	75
D412	TENSILE (psi)	400 nom.
	ULTIMATE ELONGATION (%)	220 nom.
TEMPERATURE RANGE (general guideline)		-20° to 180° F -29° to 82°C
Maximum pieces per roll : 1		
Width tolerance: -0 / + 1"		
Length tolerance: -0 / + 6"		
Durometer tolerance:± 7 points		
Material is within RMA commercial gauge tolerances.		

Please ensure the product meets your application specification prior to order placement.
Specifications are subject to change without notice. The website version prevails.